

Protection Capability Assessment of Nuclear Emergency Medical Shelter

Heng Lu*, Meng Wang, Maolin Xiong, Yi Gu, Qingxian Zhang, Liangquan Ge

College of Applied Nuclear Technology and Automation Engineering, Chengdu University of Technology, Chengdu, China Email: *lh752061402@vip.qq.com

How to cite this paper: Lu, H., Wang, M., Xiong, M.L., Gu, Y., Zhang, Q.X. and Ge, L.Q. (2020) Protection Capability Assessment of Nuclear Emergency Medical Shelter. *Open Access Library Journal*, **7**: e6834. https://doi.org/10.4236/oalib.1106834

Received: September 17, 2020 Accepted: October 6, 2020 Published: October 9, 2020

Copyright © 2020 by author(s) and Open Access Library Inc. This work is licensed under the Creative Commons Attribution International License (CC BY 4.0). http://creativecommons.org/licenses/by/4.0/

Abstract

The Monte Carlo model of the nuclear emergency medical shelter was set according to the national standard. The absorbed dose of ICRU balls, on behalf of emergency personnel in the shelter, caused by major radionuclides (⁶⁰Co, ⁸⁵Kr, ¹³¹I, ¹³³Xe, ¹³⁷Cs) in the air around nuclear facilities was obtained by Monte Carlo simulation. The functional relationship between the maximum working time of emergency rescuers in the shelter and the activity concentration of radionuclide outside the shelter was given. Taking ¹³⁷Cs as an example, the fitting curve of shielding lead layer quality and shielding effect was obtained according to the simulation result. When the thickness of the shielded lead layer reaches 5 mm, the working time of emergency rescuers in the shelter can be effectively improved from 1 hour to 2.5 hours under the activity concentration of 7.72E+09 Bq/m³.

Subject Areas

Nuclear Physics

Keywords

The Nuclear Emergency Medical Shelter, ICRU Ball, Working Time, Effective Dose, Activity Concentration

1. Introduction

The nuclear emergency medical shelter can be used to transport and provide effective protection for equipment and personnel in an emergency. The design schemes of medical shelter applicable to automobiles and ships have been proposed for a long time [1]-[6]. Most of these schemes are designed for military fields. Otherwise, these schemes do not consider the effective doses of the rescuers inside the shelter during the rescue process. Therefore, in the design of the nuclear emergency medical shelter, it is necessary to consider that the shielding effect of it to ensure the effective dose of the rescuers in the nuclear emergency event is within the allowable range.

In this paper, the radiation protection capability of a medical designed according to the GBJ 6109-2007 CAF60 standard shelter was assessed. The absorbed dose of humans in the shelter caused by radionuclides around nuclear facilities air was simulated by Monte Carlo method. The functional relationship between the working time in the shelter and the activity concentration of radionuclide outside the shelter is given under the precondition of the guidance values for the exposure dose of emergency response workers. In order to increase the effective working time of emergency rescuers in the shelter in the nuclear emergency, a shielding lead layer was added in the shelter with the examples of ¹³⁷Cs. It provides a basis for shielding design of nuclear emergency medical shelter.

2. Physical Model of Medical Shelter

The model of the nuclear emergency medical shelter was set according to the GBJ 6109-2007 CAF60 standard, as shown in **Figure 1**. The size of the medical cabin body is 6.058 m \times 2.438 m \times 2.100 m. 1.5 mm thick aluminum was distributed both inside and outside the shelter, 49 mm thick polyurethane in the middle. Two ICRU balls were set in the middle and edge shelter to represent the human tissue.

3. Calculation Method of Human Absorbed Dose

Around nuclear facilities, the radionuclides in the air mainly exist in the form of gaseous (85 Kr and 133 Xe) or aerosol (60 Co, 131 I, and 137 Cs) [7] [8] [9] [10] [11]. The energy and release probability of these radionuclides γ rays is shown in **Table 1**. The simulation was completed by MCNPX. To reasonably estimate the human



Figure 1. Model of nuclear emergency medical shelter.

Table 1. Rdionuclide ray energy and its release probability.

Radionuclides	Energy (γ)/keV	Total release probability
⁶⁰ Co	1170, 1330	2.00
¹³⁷ Cs	661	0.85
⁸⁵ Kr	514	0.43
¹³¹ I	30, 80, 177, 284, 364, 503, 637, 773	0.97
¹³³ Xe	31, 81, 161, 223, 303, 384	0.84

absorbed dose, the ICRU ball represented the body membrane, and *F6 card, a tool to calculate the average deposition energy over a cell in MCNPX program, was used for recording. The ICRU ball was set according to ICRU specifications, with a density of 1 g/cm³ and a diameter of 30 cm. The mass percentages of hydrogen, carbon, nitrogen, and oxygen are 10.1%, 11.1%, 2.6%, and 76.3%, respectively.

The result recorded by *F6 card is the contribution of each source particle to the tissue absorbed dose called the normalized absorbed dose D_0 [jerks/g].The source unit activity dose rate \dot{D}_0 [(nGy/h)/Bq] is calculated and then converted into unit concentration absorbed dose rate \dot{D}_1 [(nGy/h)/(Bq/m³)].

$$\dot{D}_0 = D_0 \times 1 \times Q \times 10^9 \times 10^9 \times 3600 \times 10^3 \tag{1}$$

$$\dot{D}_1 = \dot{D}_0 \times V \times 1 \tag{2}$$

Q is the expected value of the γ ray emission probability per unit activity of the radionuclide, while *V* is the sampling volume (m³) of the geometric model radioactive source.

The dose rate of human tissue in the medical shelter can be calculated by the following formula:

$$\dot{D} = \dot{D}_1 \times A \tag{3}$$

A is the activity concentration of the radionuclide in the air.

Then the effective dose of the human body from R-type radiation within t time can be expressed as:

$$E = \sum_{T} \sum_{R} W_{T} \times W_{R} \times \dot{D}_{1} \times A \times t$$
(4)

 W_T is the tissue weighting factor of human tissues *T*. W_R is the radiation weighting factor of R-type radiation. For γ radiation, the value of W_R is 1.

4. Dose Estimation

When simulating and calculating the absorbed dose of human in the shelter caused by radionuclides, medical shelter is placed on the ground. While the inside and outside of the shelter are air, and the radionuclides are evenly diffused in the air. The sampling simulation of radioactive materials in the extravehicular atmosphere is set as a cube space. To improve the efficiency of simulation calculation while ensuring the accuracy of sampling, it is necessary to establish the saturation boundary. Refer to the theoretical formula (5), the attenuation ratio of different energy rays in the air was calculated.

$$I = B \times I_0 \times e^{-\mu_m \times X_m} \tag{5}$$

 X_m is the travel distance of γ ray in the air; B is the accumulation factor; μ_m is the mass attenuation coefficient of γ ray in the air; I and I_0 are the energy of γ ray before and after X_m travel distance in the air.

According to the changing trend of attenuation intensity with γ -ray travel distance, the side lengths of the sampling boundary are set differently, as shown

in Table 2.

4.1. Dose Caused by Aerosol Radionuclides outside the Shelter

The radionuclides are evenly distributed in the air outside the shelter. According to the formulas in chapter 3, \dot{D}_0 and \dot{D}_1 caused by aerosolradionuclides were calculated, as shown in Table 3.

4.2. Dose from Inert Radionuclides inside and outside the Shelter

The medical shelter is designed with an air filtration purification system; however, the inert gas is difficult to filter out. At this time, the concentration of inert radionuclides inside and outside the medical cabin tends to be the same. According to the formulas in chapter 3, \dot{D}_0 and \dot{D}_1 caused by inert gas radionuclides were calculated, as shown in **Table 4**. The absorbed dose rate of human tissues caused by the unit concentration of inert radionuclides in the shelter is far lower than that caused outside the shelter.

4.3. Evaluation of Radiation Protection Capability of Medical Shelter

The guidance values for the exposure dose of emergency rescuers are shown in **Table 5** according to the standards promulgated by IAEA in 2014 [12].

Radionuclides	Length of the sampling boundary/m	
⁶⁰ Co	800	
⁸⁵ Kr	600	
¹³¹ I	400	
¹³⁷ CS	600	
¹³³ Xe	300	

Table 2. The side length of the outer cube sampling boundary of different radionuclides.

Table 3. Simulation results of absorbed dose induced by outside radionuclides.

	Site	Normalized absorbed dose/jerks·gram ⁻¹ ·nps ⁻¹	RSD/%	Absorbed dose rate per unit concentration/nGy·h ⁻¹ ·(Bq/m ³) ⁻¹
⁶⁰ Co	Middle	2.27E-34	±5.34	3.28E-01
	Side	2.28E-34	±5.35	3.31E-01
137.0-	Middle	2.51E-34	±3.71	6.47E-02
¹³ /Cs	Side	2.43E-34	±3.81	6.28E-02
8517	Middle	1.93E-34	±3.77	2.53E-02
⁶⁵ Kr	Side	1.97E-34	±3.70	2.59E-02
1311	Middle	3.63E-34	±2.46	3.19E-02
1	Side	3.66E-34	±2.48	3.21E-02
13337	Middle	7.14E-35	±2.86	2.29E-03
Xe	Side	7.82E-35	±2.79	2.51E-03

To ensure that the dose of emergency rescuers is within the guidance value, the protective performance of the medical shelter is necessary to be evaluated. The relationship between the maximum working time of emergency rescuers in the medical shelter and the concentration of radionuclides outside the shelter within the guideline value was obtained according to formulas in chapter 3. The rescuers in the shelter are irradiated uniformly; therefore, the value of the tissue weighting factor W_T is 1. In contrast, the guide value of the radiation dose for emergency rescuers is 500 mSv.

$$=\frac{500\times10^{-3}}{\dot{D}_{1}\times A\times10^{-9}}$$
(6)

t is the working time of emergency rescuers, while *A* is the activity concentration of radionuclide outside the shelter. Introducing the coefficient $K = \frac{5 \times 10^8}{\dot{D}_1}$:

$$t = \frac{K}{A} \tag{7}$$

The value of *K* without lead shield was shown in **Table 6**.

t

Table 4. Absorbed dose rate due to inert radionuclides.

	Site	Absorbed dose rate per unit concentration the outside/nGy·h ⁻¹ ·(Bq/m ³) ⁻¹	Absorbed dose rate per unit concentration the inside/nGy·h ⁻¹ ·(Bq/m ³) ⁻¹
⁸⁵ Kr	Middle	2.53E-02	4.75E-04
	Side	2.59E-02	4.29E-04
¹³³ Xe	Middle	3.19E-02	7.48E-04
	Side	3.21E-02	6.77E-04

Table 5. The guidance values for the exposure dose of emergency response workers.

Emergency action	The guidance values
Action to save the life	<500 mSv
Actions to prevent the severe deterministic effect	<500 mSv
Actions to prevent disasters that may have a major impact on humans and the environment	<500 mSv
Actions to avoid large collective doses	<100 mSv

 Table 6. Value of K without lead shield.

Radionuclide		Value
⁶⁰ Co	Middle	1.52E+09
	Side	1.51E+09
¹³⁷ Cs	Middle	7.72E+09
	Side	7.96E+09
¹³¹ I	Middle	1.57E+10
	Side	1.56E+10

The influence of internal exposure needs to be considered for 85 Kr and 133 Xe. According to ICRP Document No. 61, effective dose conversion factors of 85 Kr and 133 Xe are 2.2E–11 Sv/(d·Bq/m³) and 1.2E–10 Sv/(d·Bq/m³), respectively. The relationship between the maximum working time of emergency rescuers inside the medical shelter and the concentration of radionuclides outside the shelter is expressed by the following formula.

$$t = \frac{500 \times 10^{-3}}{\left(\dot{D}_1 \times 10^{-9} + \frac{L}{24}\right) \times A}$$
(8)

Introducing the coefficient $M = \frac{500 \times 10^{-3}}{\dot{D}_1 \times 10^{-9} + \frac{L}{10^{-3}}}$:

$$t = \frac{M}{A} \tag{9}$$

The value of *M* without lead shield was shown in **Table 7**.

When the activity concentration of ¹³⁷Cs outside the shelter is 7.72E+09 Bq/m³, the maximum allowable working time of emergency rescuers in the medical shelter is one hour. To increase the maximum working time of emergency rescuers, a lead shielding layer should be added to the structural materials of the medical shelter.

5. Protection Performance Improved through the Lead Shield

Taking ¹³⁷Cs as an example. The shielding effect curve of the two ICRU balls in the shelter with being a lead shield was shown in **Figure 2**. The fitting curve can describe the relationship between the quality of the lead and the shielding effect. With the 5 mm thickness of the lead layer, the absorbed dose in the middle and edge of the shelter was reduced to 60.2% and 61.66%, respectively. At this time, the coefficient *K* in formula (7) can be calculated. The value of M within 5 mm thickness of the lead layer was shown in **Table 8**.

As shown in **Figure 3**, when the activity concentration of ¹³⁷Cs outside the shelter is 7.72E+09 Bq/m³, the maximum working time of emergency rescuers is 2.5 hours with 5 mm thickness of the lead layer. Compared with the calculation results without the lead layer, the setting of the lead layer shielding can effectively increase the working time of emergency rescuers in the medical shelter and provide sufficient time for emergency rescue.

Table 7	. Value	of M	without	lead	shield.
---------	---------	--------	---------	------	---------

Radionuclide		Value
⁸⁵ V.	Middle	1.91E+10
Kr	Side	1.86E+10
¹³³ Xe	Middle	1.79E+11
	Side	1.66E+11



Figure 2. The relationship between the shielding effect and the weight of the lead layer.



Table 8. Value of *M* with 5 mm thickness of the lead layer.

Figure 3. Working time curve of Emergency rescuers

6. Conclusion

The human absorbed dose caused by radionuclides in gases and aerosols around nuclear facilities before and after setting up the medical cabin was obtained by Monte Carlo simulation. The formula for calculating the maximum working time of emergency rescuers in the medical shelter under the guidance value of the exposure dose was given. Comparing the working time curves of the medical shelter without lead layer and that with 5 mm thickness of the lead layer, when the activity concentration of ¹³⁷Cs outside the shelter is 7.72E+09 Bq/m³, the maximum working time of emergency rescuers was increased from 1 hour to 2.5 hours.

Acknowledgements

Thanks are due to Hongjie Chen for assistance with the experiments and to Lipeng Xu for valuable discussion.

The authors acknowledge the financial support by Sichuan Province Key R & D Project (No. 16ZA0085).

Conflicts of Interest

The authors declare no conflicts of interest regarding the publication of this paper.

References

- Kuang, X.-P., Xie, X.-P. (2017) Development and Application of Second-Generation Medical Shelter of the PLA. *Chinese Medical Equipment Journal*, 38, 132-134+137.
- [2] Wang, X.-B., Luan, Z.-T., Qu, F.-X., *et al.* (2011) Development of Medical Cabin in Emergency Boat on Sea. *China Medical Devices*, 26, 71+77.
- [3] Liu, S., Tang, X.-W. and Zhu, L.-H. (2018) Nuclear Biological and Chemical Protection Design for Shelter. *Command Information System and Technology*, **9**, 96-100.
- [4] Yu, J.-P., Fan, Z.-P., Lu, Y.-J., et al. (2001) Basic Technical Design of Nuclear Accident Medical Rescue Shelter Body. *Journal of Navy Medicine*, No. 1, 79-81.
- [5] Qi, S.-B., Liu, Y., Li, F., *et al.* (2016) Research on Medical Cabin and Layout Design of a Certain Type of Surface Ship. *Chinese Journal of Nautical Medicine and Hyperbaric Medicine*, 23, 144-146.
- [6] Guo, X.-L. (2014) Research on Nuclear-Biological-Chemical Protection System of Mobile Shelter. *Fire Control & Command Control*, **39**, 115-123.
- [7] Zhou, Z., Wang, H.-N. and Shi, X.-Z. (2018) Study on Airborne Radioactive Release Control under Severe Accident Condition. *China Nuclear Power*, **11**, 417-421.
- [8] Zhong, Y.-M., Shi, X.-Z., Yang, Z.-Y., et al. (2016) Annulus Ventilation and Filtration System Mitigate Analysis of FPs Release. Nuclear Science and Engineering, 36, 504-509.
- [9] (2018) Advance in the Development of Physicochemical Models for Radioactive Aerosols from the Fukushima Daiichi Accident. *Environmental Science & Technology*, **41**, 107-113.
- [10] NEA (2000) Insights into the Control of Release of Iodine, Cesium, Strontium and Other Fission Products in the Containment by Severe Accident Management, NEA/CSNI/ R(2009)9. OECD Nuclear Energy Agency, Le Seine, France.
- [11] Chae, N., Lee, M.-H., Choi, S., *et al.* (2019) Aerodynamic Diameter and Radioactivity Distributions of Radioactive Aerosols from Activated Metals Cutting for Nuclear Power Plant Decommissioning. *Journal of Hazardous Materials*, **369**, 727-745.

https://doi.org/10.1016/j.jhazmat.2019.02.093

[12] IAEA (2014) Safety Standards for Protecting People and the Environment. Radiation Protection and Safety of Radiation Sources: International Basic Safety Standards. General Safety Requirements Part 3, No. GSR Part 3, IAEA, Vienna.